### **TUNGSRAM**

Innovation is our heritage EST. 1896





Low voltage capsule -Transversal Filament 10W 12V G4 2000HR TU BX 1/20MIH 93112560

### **Product information**

These lamps are made from a quartz material which blocks virtually all UV-B and UV-C radiation. With a transmission cut-off wavelength of between 350 and 400 nm, it is ideal for lamps requiring maximum visible transmittance with nearly complete UV protection. The lamps use doped quartz which is an effective barrier to potentially harmful ultra-violet radiation while maintaining the other high quality properties of standard clear fused quartz.

The axial filament types have been specifically developed to satisfy the demand for a wide smooth beam with a good cut-off, from a miniature linear reflector, for the uniform lighting of vertical surfaces, for table lamps for task lighting, or for wall mounted or portable uplighters. With all wattages having the axial filament at the same light centre, one luminaire design may cover a range of illuminances for a variety of residential and commercial requirements. When used in spot reflectors these lamps may also be more efficient alternatives to



### Trungsram Low voltage capsule - Transversal Filament

93112560

transverse filament types, because a substantial portion of the filament will always be in the focal point.

#### **Application** areas







# Trungsram Low voltage capsule - Transversal Filament

93112560

#### Product data

Product Code	93112560
Bulb Shape	Tubular
Bulb Diameter [mm]	9
Maximum Overall Length [mm]	33
Net weight per piece [g]	12
Gross weight per piece [g]	14
Brand	Tungsram
Cap/Base	G4

#### Performance data

Rated Lumens [lm]	145
Weighted energy consumption [kWh/1000h]	10.6
Rated efficacy [lm/W]	14
Energy efficiency class (EEC)	G
Lamp Lumen Maintenance factor (2000 hours)	80%
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]]	2800
Nominal lumens [lm]	145
Colour Rendering Index (CRI) [Ra]	100



# Trungsram Low voltage capsule - Transversal Filament

93112560

#### Electrical data

Rated power [W]	10.0
Starting time (sec)	0.0 s
Warm up time up to 60% of full light output	instant
Number of switching cycles	8000
Coil type	C-6
Dimming Capability	Yes
Nominal power [W]	10
Nominal lamp voltage [V]	12

### Logistic data

Shipment	Standard
DUN Code	15994100031076
EAN Code	5994100031079
Pack Quantity	20
Inner pack type	BX
Outer pack type	ОВ
Layer quantity	6400 EUR, 8400 UK
Layer quantity EUR	6400
Layer quantity UK	8400
Pallet quantity EUR (PC)	32000
Pallet quantity UK (PC)	42000
Outer case size	131 x 90 x 40 (mm)
Product status	Available



# **Transversal Filament**

93112560

#### Downloads & Links

Go to the catalog site (HTTP) Halogen Lamps Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)