



## PRODUCT DATA SHEET

<b>Hood PE 1500 / 600 / 600 / x 2000x0.06 black (109352)</b>		<b>Version 4</b>
<b>WFKA0955</b>	<b>Norengros</b>	Issue date: <b>09.02.2024</b>

### 1. PRODUCT PROPERTIES<sup>1</sup>:

Parameter	Value	Deviation	Unit	Methodology
Thickness	60	$2\sigma \pm 5\%$	$\mu$	PN-ISO 4593
Width	1500	$\pm 20$	mm	PN-ISO 4592
Width of gussets	600		mm	PN-ISO 4592
Length	2000	$\pm 1\%$	mm	PN-ISO 4592
Density	947	5%	kg/m <sup>3</sup>	PN-EN ISO 1183-2
Transmittance	Not tested <sup>2</sup>	$\pm 4$	%	ASTM D1003
Haze	Not tested <sup>2</sup>	$\pm 4$	%	ASTM D1003
Clarity	Not tested <sup>2</sup>	$\pm 4$	%	ASTM D1003

<sup>1</sup> Film made of PE.

<sup>2</sup> Tests are performed based on client's individual request.

### 2. MECHANICAL PROPERTIES:

Parameter	Value	Deviation	Unit	Methodology
Tensile at break: - lengthwise - crosswise	Not tested <sup>2</sup>	—	MPa	PN-EN ISO 527-3
Tensile at yield point: - lengthwise - crosswise	Not tested <sup>2</sup>	—	MPa	PN-EN ISO 527-3
Elongation at break: - lengthwise - crosswise	Not tested <sup>2</sup>	—	%	PN-EN ISO 527-3
Coefficient of friction: - static - dynamic	Not tested <sup>2</sup>	—	—	PN-EN ISO 8295
Dart- drop	Not tested <sup>2</sup>	—	g	PN-EN ISO 7765
Breaking force at the seal	Not tested <sup>2</sup>	—	N/25 mm	ASTM F2029-08

### 3. PACKAGING:

Film on a paper core or on PVC core with diameter of 76x12, covered with PE film and placed on a pallet 800x1200.

### 4. APPLICATION:

Film for food packaging purposes.

### 5. STORAGE:

Film should be protected against atmospheric factors and be stored not longer than 24 months.

Prepared by: Marta Hirowska	Confirmed by: Jarosław Pawlik